

Declaration of Performance



No. DoP673004 Skamol Smooth Plaster

- 1. Unique identification code of the product-type:**
Skamol Smooth Plaster
- 2. Intended use of construction product:**
Intended for use on walls, ceilings and partitions, in particular as mineral filler used for silicate-limestone panel
- 3. The manufacturer's name and address:**
Skamol A/S
Hasselager Centervej 1,
8260 Viby, Denmark
- 4. The authorized representative's name and address:**
NPD
- 5. Systems of assessment and verification of constancy of the performance (AVCP):**
The product is CE marked according to EN 998-1:2016, "Specification for mortar for masonry – Part 1: Rendering and plastering mortar" under AVCP-System 4.
- 6. Notified body tasks, if relevant:**
NPD
- 7. Declared performance:**

| Essential characteristics | Performance | Harmonized technical specification |
|---------------------------------------|---|------------------------------------|
| Reaction to fire: | Class A1 | EN 998-1:2016, [IDT] |
| Adhesion (value and fracture pattern) | ≥0.08 N/mm ² FP:B | EN 998-1:2016, [IDT] |
| Thermal conductivity/Density | 0.33 W/m·K (tab. mean value, P=50%, according to EN 1745: 2012, Tab. A.12) / 1200 kg/m ³ | EN 998-1:2016, [IDT] |
| Dangerous substances | NPD | EN 998-1:2016, [IDT] |

- 8. The performance of the construction product referred to in point 1, is consistent with the declared performance in point 7.**
This declaration of performance is issued under the regulation (EU) No.305/2011 and under the sole responsibility of the manufacturer, listed in point 3. Signed for and on behalf of the production by:

Søren Nørgaard Bertel
Vice President R&D
Skamol A/S,
28-09-2023 rev1

Skamol

Hasselager Centervej 1, 8260 Viby, Denmark
Tel.: +45 97 72 15 33
www.skamol.com

