

Declaration of Performance

11.6.1.i Issue 3

1	Product Name	Viking 280
2	Description	Protect V280 is grey in colour on the upper and on the lower surface incorporating a microporous film, printed with product branding and batch numbering for identification.
3	Intended/Type of Use	Vapour permeable underlay for use in roof and wall constructions.
4	Manufacturer	Komproment, Jellingvej 11, DK9230 Svenstrup, Denmark
5	Distributor	Komproment, Jellingvej 11, DK9230 Svenstrup, Denmark
6	System of Assessment	System 3
7	Performance to hEN	Notified Test Laboratory ID Number 0338 has undertaken type testing on the essential requirements listed in the hEN Clause ZA.4
8	Performance to ETA	Not applicable

Essential Characteristics	Declared Performance		hEN
	MD	CD	
Weight	267(-36)gsm		EN 13859-1 & 2: 2014 All performances quoted are to the relevant standards contained therein
Water Resistance unaged	W1		
Water Resistance aged	W1		
Tensile Strength unaged	550(-40) N/50mm	590(-40)N/50mm	
Tensile Strength aged	530(-20) N/50mm	570(-20) N/50mm	
Elongation unaged	70(+15)%	70(+15)%	
Elongation aged	65(-15)%	58(-20)%	
Tear Resistance	400(-50N)	400(-50)N	
Flexibility at low temperature	-40 degrees		
Resistance to penetration of air	0.0m ³ /hr/m ² @50Pa		
Water Vapour Resistance unaged	≤0.10MNs/g,	≤0.02s _d (m)	
Reaction to Fire	NPD Class F		
Resistance to water penetration	>200cm		EN ISO 20811

10 The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer in point 4.

Signed for and on behalf of the distributor by: **Lars Højgaard** Date **15nd May 2017**

Name  Site

Position **Technical Manager**