

**DECLARATION OF PERFORMANCE
No. 0003DADOGRES**

- 1) Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product
Dry-pressed ceramic tiles, with water absorption $E_b \leq 0,5\%$
- 2) Intended use(s)
For internal and external walls and flooring
- 3) Name or registered trade mark, and contact address of the manufacturer
Antica Ceramica Rubiera Via Salvaterra 18/A – 42028 Rubiera (RE) Italy
- 4) System(s) of assessment and verification of constancy of performance (AVCP)
Systems 4
- 5) Name and identification number of notified laboratory, if relevant –**Not applicable**
Task(s) carried out
AVCP system
Document issued ad date of issue
- 6) Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A1 FL/A1	EN 14411:2016
Release of dangerous substance, for:		
-Cadmium	NPD	
-Lead	NPD	
Breaking strength	>1 300 N	
Slipperiness:		
PTV Slider57,CENT/TS 16165:2011 Annex C	NPD	
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive type C2	1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- Internal use	Pass	
- External use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by Emanuele Frascari Amministratore Delegato

Firma



Dado Ceramica Srl

Via Sicilia, 21 40017 San Matteo della Decima (BO) ITALY Codice fiscale 03338740370 Partita I.V.A. 00613401207

Internet: www.dadoceramica.it Tel. +39 051 6819611 - Fax +39 051 6819650



DADO CERAMICA S.r.l.
Via Sicilia 21
40017 San Matteo della Decima (BO)
ITALY

5

0002DADOGRES

EN 14411:2012

Piastrelle di ceramica pressate a secco, con
assorbimento di acqua $E_b \leq 0,5\%$, per
pavimento e rivestimenti interni ed esterni