Product data sheet

Product category	Mini splits
Brand	Qlima
Model	MS-AC 5002
Colour	White / Black
EAN code	8713508792729

Technical specifications

|		
EER	W/W	2,6
Energy class		A
Energy consumption - hourly indicative (Qsd/c)	kWh	
Power supply	V/Hz/Ph	220-240~ / 50 / 1
Current nominal	A	2,5
Rated power cooling	kW	1,46
Airflow	m³/h	280
Adjustable air flow - vertical		Yes
Dehumidification capacity	l/24 h	—
Operating range	°C	~
Thermostatic range	°C	16 ~ 30
Sound pressure noise level at 1 m - high mode (SPL)	dB(A)	52,3
Sound pressure level-silent mode		39
Fan speeds	positions	2
Control		electronic / Wi-Fi
Air filter	type	Screen
Refrigerant type / GWP / Charge	R/g	R290 / 3 / 130
For rooms up to	m³	40 - 45
Compressor type		
CO_2 equivalent	tonnes	0,00039
Protection class		IP24
Dimensions indoor unit (w x d x h)	mm	455 x 175 x 326
Dimensions outdoor unit (w x d x h)	mm	460 x 212 x 363
Net. weight - indoor unit	kg	6,5
Net. weight - outdoor unit	kg	13
Net. weight	kg	20
Warranty	year	2

All data is measured in accordance with applicable EU specified standards at the time of production. To be used for indicative purposes only.

Package content

Outdoor unit, Indoor unit, Wall bracket , Drainage tube, Tube cover, User manual

Accessories (to order)

Description	EAN code

guarantee
2 YEARS

20 ft = 220
40 ft = 460
40 HQ = 480

W x D x H =
52 x 51 x 46 cm

Gross weight
25 kg

Qlima

MS-AC 5002

Mini split unit air conditioner

Sleep mode

Dehumidifier function

Very silent

Timer function

Adjustable airflow

WiFi functionality

Wireless smart control: The air conditioner is equipped with Wi-FI for extra comfort and to save energy. With the smart Tuya app you can start, stop or operate the main functions of the air conditioner remotely.

Air conditioning: In COOLING mode the unit produces a refreshing cool airflow.

Dehumidifying: In DRY mode the unit extract excessive moist from the room. Note: In COOLING mode the air is also dehumidified.

Refrigerant gas R290: Natural gas with high energy efficiency. Environmentally friendly, R 290 gas has a neutral impact on the ozone layer.

Fan speed setting: The airconditioner has multiple speed setting. The LCD display on the remote control will show the chosen speed.

Timer: Timer function can be set between 30 minutes and 24 hours (Timer On or Timer Off).

White carton box: The unit is delivered completely with all auxiliary parts.

Plug &

Play: The unit doesn't require installation. Position the unit in the window frame, plug it in and enjoy instant cooling.