

## **Declaration of Performance**



DoP-e13/0416

1. Product Type: Bonded Anchor / Injection System

2. Identification: AT-HP (Masonry)

3. Intended Use: Refer to ETA-13/0416, Section 1.2

4. Manufacturer: Simpson Strong-Tie Int. Ltd

For local branch addresses refer to www.strongtie.eu

5. Authorised Representative: N/A

6. System of Assessment: 1

7, 8. Technical Specifications & Notified Bodies:

	Name	No.	System of Assessment	Document Reference	EAD (ETAG) No. EN Standard
Technical Assessment	ZAG	-	1	ETA-13/0416	ETAG 029: 2013
Assessment and Verification of Constancy of Performance	CSTB	0679	1	0679-CPD-0899	-

9. Declared Performance:

Essential Characteristics	Performance	ETA Clause; EN or ISO Standard	
Mechanical Resistance & Stability	ETA-13/0416	ETA Chapter 2 & Annexes 6 to 12	
	ETAG 029, Annex C		
Reaction to Fire (Class)	NPD	-	
Resistance to Fire	NPD	-	
Hygiene, Health and the Environment	Refer to Product Label and	EC 1907/2006 - REACH	
riygiene, riealti and the Environment	Safety Data Sheet		
Safety in Use	NPD	-	
Protection against Noise	NPD	-	
Energy, Economy & Heat Retention	NPD	-	
Durability		ETA Section 1.2 & Annex 8	
	Zinc Electroplated: ≥ 5 µm	EN ISO 4042; EN ISO 898-1 & -2	
	Hot Dip Galvanised: > 40 μm	EN ISO 10684; EN ISO 898-1 & -2	
	Stainless Steel:		
	A4-70 & HCR-70	EN 10088; EN ISO 3506-1 & -2	
Serviceability	Refer to ETA	ETA Annex 11	
Identification	Refer to Point 2. & ETA	ETA Section 1.1 & Annexes 1,2,3 & 8	

(NPD - No Performance Determined)

The performance of the products identified in points 1. & 2. is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Laurent Versluysen European Managing Director

(Sainte Gemme La Plaine, Fr. 01/07/2013)