

1. Unique identification code of the product-type: **Corrugated bitumen sheets**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR: **corrugated bitumen sheets category S 3**. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: **Discontinuously laid roof coverings for buildings**
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): **ONDULINE FRANCE –Rue du Bac- BP15 – 76480 YAINVILLE – FRANCE – Tel 00 02 35 05 90 90 – Fax 00 02 35 05 91 11– email : info@onduline.fr**
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable**
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 4**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard : **Not applicable**
8. Declared performance

Essential characteristics	Performance	Harmonized technical specification
Bending under downward load	Category S : >700N/m ²	EN 534 (2010)
Impact strength	Category S : 250 mm	
Tearing strength	Category S: > 150 N	
Water permeability	Pass	
Tearing strength after freeze/thaw ageing	Category S: > 150 N	
Water permeability after freeze/thaw ageing	Pass	
Thermal coefficient	$\alpha < 100 \times 10^{-6} \text{ 1/K}$	
Reaction to Fire	E	
External fire performance	F	
Dangerous substances	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.


This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

DUBUC PASCAL Executive Director

Yainville, 01st of July 2013




ONDULINE FRANCE –Rue du Bac- BP15 – 76480 YAINVILLE – FRANCE 03
DoP 03-002 2013-07-01
EN 534 : 2010
Corrugated bitumen sheets for roof covering and wall finishing Category S
Bending under downward load : > 700 N/m²
Impact strength: 250 mm
Tearing strength : >150 N
Water permeability: pass
Tearing strength after freeze/thaw ageing : >150 N
Water permeability after freeze/thaw ageing: pass
Thermal coefficient : <100 x 10⁻⁶ 1/K
Reaction to Fire : E
External fire performance F
Dangerous substance X : NPD

<i>CE marking, consisting of the “CE”-symbol</i>
<i>name and the registered address of the manufacturer, or identifying mark</i>
<i>Last two digits of the year in which the marking was first affixed</i>
<i>Reference number of the DOP (see note 16)</i>
<i>No. of European standard applied, as referenced in OJEU (see note 19)</i>
<i>Unique identification code of the product-type</i>
<i>Intended use of the product as laid down in the European standard applied</i>
<i>Level or class of the performance declared</i>

Figure ZA.5 — Example CE marking information of products under AVCP system 4