

DECLARATION OF PERFORMANCE (DoP)

No. 001GP

1. Unique identification code of the product type

Dry-pressed ceramic tiles, with water absorption Eb ≤ 0,5%

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

Gambini Group S.p.A.

Via Radici in Piano 675 41049 Sassuolo (MO) Italy

4.System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

5. Name and identification number of notified laboratory

NPD

6.Declared performances

Essential characteristics	Performance	Harmonised tecnical specification
Reaction to fire	A1 _{FL}	
Release of dangerous substance, for:		
-Cadmium	NPD	
-Lead	NPD	
Modulus of rupture	Modulus of rupture average >35N/mm2	
	Single value >32N/mm2	
Slipperiness:	See Table Attached	EN 14411:2012
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitious adhesive, type C2	NPD	
Thermal shock resistance	Pass	
Durability for:		
internal use:	Pass	
external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by:

Place and date of issue

Enzo Gorlero (Technical director)

Version 11/11/2016 Page 1 / 1



Gambini Group S.p.A. Via Radici in Piano 675 41049 Sassuolo (MO) Italy

05

001GP

EN 14411:2012

Dry-pressed ceramic tiles, with water absorption $E_b \le 0.5\%$, for internal and external walls and floorings