

Declaration of Performance



No. DoP74410 Skamol Lime Mortar

- 1. Unique identification code of the product-type:**
Skamol Lime Mortar
- 2. Intended use of construction product:**
New construction/Renovation: Adhesive, finishing, grouting and plastering for interior.
- 3. The manufacturer's name and address:**
Skamol A/S
Hasselager Centervej 1,
8260 Viby, Denmark
- 4. The authorized representative's name and address:**
NPD
- 5. Systems of assessment and verification of constancy of the performance (AVCP):**
The product is CE marked according to EN 998-1:2016, "Specification for mortar for masonry – Part 1: Rendering and plastering mortar" under AVCP-System 4.
- 6. Notified body tasks, if relevant:**
NPD
- 7. Declared performance:**

| Characteristics | Performance | Harmonized technical specification |
|------------------------------------|---|------------------------------------|
| Mixing ratio | | |
| Hydrated lime | 35 kg | |
| Hydraulic Lime (NHL) | 65 kg | EN 998-1:2016 |
| Quartz sand | 499 kg | |
| Natural Latex | < 1% | |
| Chloride content | < 0,1% | EN 998-1:2016 |
| Reaction to fire | Class A1 | EN 998-1:2016 |
| Water absorption | NPD | EN 998-1:2016 |
| Water vapor permeability | NPD | EN 998-1:2016 |
| Thermal conductivity (table value) | 0,90 W/mK | EN 998-1:2016 |
| Durability against frost/thaw | Durability in exposure classes MX1 to MX 4 | EN 998-1:2016 |

- 8. The performance of the construction product referred to in point 1, is consistent with the declared performance in point 7.**

This declaration of performance is issued under the regulation (EU) No.305/2011 and under the sole responsibility of the manufacturer, listed in point 3. Signed for and on behalf of the production by:

Søren Nørgaard Bertel
Vice President R&D
Skamol A/S,
5-07-2023 rev0

Skamol A/S

Hasselager Centervej 1, 8260 Viby, Denmark
Tel.: +45 97 72 15 33

www.skamol.com

