Declaration of performance No. 5002

			LIP VS 30 Watertight covering kit	
Intended uses:		Liquid applied watertight covering kit for wet room floors and walls		
Manufacturer:		LIP Bygningsartikler A/S, Industrivej 16, 5580 Nørre Aaby, Denmark		
System/s of AVCP:		2+		
European Assessment Document:		Guideline for European Technical Approval (ETAG) No. 022 Watertight covering kits for wet room floor and/or walls, Part 1 Liquid applied coverings with or without wearing surface, edition April 2007, used as European Assessment Document (EAD).		
European Technical Assessment:		ETA-12/0025 of 05/03/2017		
Technical Assessment Body		ETA-Danmark A/S		
Notified body:		1073		
Declared per	formance			
Reaction to fire		NPD		
Release of dangerous substances		No dangerous materials		
Vapour permeability		RH 100 \rightarrow 75 %: $Z_p = 220.1$ GPa \cdot s \cdot m ² /kg and equivalent $s_d = 43.0$ m		
		RH 93 \rightarrow 50 %: Z _p = 223.6 GPa \cdot s \cdot m ² /kg and equivalent s _d = 43.7 m		
Water tightness		Pass		
Crack bridging ability		Category 2		
Bond strength		Category 2 (≥ 0.5 MPa) for concrete substrate		
		Category 1 (≥ 0.3 MPa) for other materials as described in clause 2 in ETA-12/0025		
Scratching resistance		NPD		
Joint bridging ability		Category 2		
Water tightness around penetrations		Category 2		
Resistance to temperature		Category 2 (≥ 0.5 MPa)		
Resistance to water		Category 2 (≥ 0.5 MPa)		
Resistance to alkalinity		Category 2 (≥ 0.5 MPa)		
Reparability		NPD		
Thickness		Minimum thickness of the membrane: 0.58 mm		
Applicability		Applicable		
Sustainable use of natural resources		NPD		
declaration of		with Regu	ty with the set of declared performances. This lation (EU) No 305/2011, under the sole red on behalf of the manufacturer by:	
Name	Kristian K. Mortensen	Date	15/08/2017	
Signature	(hich (). Wohn	Place	Nr. Åby	