

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011
(Construction Products Regulation)

Nr. DoP-DE-multi 292

- Unique identification code of the product-type:*
weber.multi 292
Lightweight rendering mortar LW according to DIN EN 998-1
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):*
Batch/production date/production site/serial No. is printed on packaging or accompanying documents
- Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*
Lightweight rendering mortar LW for internal use on walls, ceilings, columns and partitions
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):*
Saint-Gobain Weber GmbH
Schanzenstr. 84
D-40549 Düsseldorf
www.sg-weber.de
- Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):*
not applicable
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:*
System 3 (Reaction to fire)
System 4
- In case of the declaration of performance concerning a construction product covered by a harmonised standard:*
The notified body Materialprüfungsamt Nordrhein-Westfalen, identification number No. 0432, performed the determination of the class regarding reaction to fire on the basis of product testing under system 3 and issued: test report No. 230008550-4.
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:*
not applicable

9. Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A 1	DIN EN 998-1:2010-12
Water absorption	W 2	
Water vapour permeability μ	≤ 20	
Adhesion	$\geq 0,08 \text{ N/mm}^2$ (FP B)	
Thermal conductivity $\lambda_{10, \text{dry, mat}}$ (Tab. value EN 1745)	$\leq 0,39 \text{ W/(m}\cdot\text{K)}$ (P=50%) $\leq 0,43 \text{ W/(m}\cdot\text{K)}$ (P=90%)	
Durability	NPD	
Dangerous substances	NPD	

NPD (No Performance Determined)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Bruno Reisch, Direktor Technik

Düsseldorf, May 30, 2014
(Place and date of issue)

ppa Reisch
(Signature)

Annex
Material safety data sheet weber.multi 292