

Accessories (each sold separately)

Mini-Rider		
Twin bagger for Troy-Bilt® Mini-Rider with 76 cm decks, capacity 115 l		Mod. no.: 19A300140EM
Mulch Kit/deflector with blade for Troy-Bilt® Mini-Rider with 76 cm decks		Mod. no.: 196-334-600
Rear hitch for Troy-Bilt® Mini-Rider with side discharge		Mod. no.: 196-397-000
Rear hitch for Troy-Bilt® Mini-Rider with rear discharge		Mod. no.: 196-398-000

Lawntractors		
Twin bagger for Troy-Bilt® side discharge lawn tractors, 229 l, for 92 cm decks		Mod. no.: 19A300450EM
Twin bagger for Troy-Bilt® side discharge lawn tractors, 229 l, for 107 cm decks		Mod. no.: 19A300310EM
Mulch Kit (without blades)		Mod. no.: 196-749A678
Rear deflector for Troy-Bilt® rear-discharge models		Mod. no.: 196-750A678
Rear hitch for Troy-Bilt® lawn tractors with rear discharge		Mod. no.: 196-399-000
Front bumper, fits all Troy-Bilt® lawn tractors		Mod. no.: OEM-190-679
Battery charger for all Troy-Bilt® lawn tractors		Mod. no.: 196-967-678
Chevron style rear wheels 18" x 9,5". Set consists of 2 cpl. wheels. Fits all Troy-Bilt® lawn tractors with either 18" or 20" rear wheels.		Mod. no.: 196-721A678
117 cm dozer blade		Mod. no.: 19A300170EM
Rubber lip for dozer blade 19A300170EM		Mod. no.: 196-718-678
Tire chains for 18" x 9,5" wheels incl. adapter (rear discharge models)		Mod. no.: 196-898-699
Tire chains for 20" x 8,0" wheels incl. adapter (side discharge models)		Mod. no.: 196-658-699



Stanley Black & Decker Outdoor GmbH, Wiesenstraße 9, D-66129 Saarbrücken, Germany

Germany: Phone +49 (0)681 96 98 90 68, mtd.de@mtdproducts.com
Austria: Phone +43 (0)720 81 60 87 – mtd.at@mtdproducts.com
Switzerland: Phone +41 (0) 43 588 13 58 – mtd.ch@mtdproducts.com

© 2023 Stanley Black & Decker Outdoor GmbH, Germany
Text and photographs, specifications of dimensions and performance are composed with greatest care. The correctness of the information cannot be guaranteed, especially it is not guaranteed that the products comply with the images regarding technique, colour, form and equipment or that the products comply with the proportion of the images. Amendments due to misprints or errors are reserved.
This Troy-Bilt® catalogue is valid from September 2023.

As of 09-2023



Product Program 2024

Pretty agile, these little ones!

When it comes to mowing lawns and meadows with lots of shrubs, trees, or other obstacles, you'll truly appreciate the advantages of a Mini-Rider: agile and flexible with a small turning radius, robustly built, and powered by a strong engine. The new Troy-Bilt® Mini-Riders feature a 76 cm wide cutting deck, allowing you to efficiently tackle areas of up to 3,000 square meters per hour* in no time. You can choose between models with side discharge or rear discharge, and both come equipped with a powerful 382cc Troy-Bilt® engine and a 6-speed transmatic drive. Simply select your gear and start mowing. And it can mow in reverse, making your work fast. So, which model will you choose?



	TB 76T-S	TB 76T-R
Engine type	TROY-BILT	TROY-BILT
Engine displacement	382 cm³	382 cm³
Rated power	7,9 kW / 2900 min ⁻¹	7,4 kW / 2700 min ⁻¹
Transmission / Speeds	Transmatic / 6 (f/b)	Transmatic / 6 (f/b)
Tank volume (capacity)	4,9 l	4,9 l
Recommended lawn area* (up to)	3000 m²/h	2500 m²/h
Cutting width / height (min.-max.)	76 cm / 38–95 mm	76 cm / 38–95 mm
Deck height adjustment	5 positions	5 positions
Deck engagement	mechanical, by lever	mechanical, by lever
Wash nozzle/Mulch Kit	Standard/optional (196-707-678)	Standard/optional (196-707-678)
Bag (capacity)	optional (19A300140EM)	150 l
Grass deflector	Standard	optional
Turning radius	46 cm	46 cm
Mow in reverse	Standard	Standard
Wheel size (f/r in inch)	13 x 5 / 16 x 6,5	13 x 5 / 16 x 6,5
Front Bumper	Standard	Standard
Headlights	–	–
Rear Hitch	optional (196-397-000)	optional (196-398-000)
Replacement blades	742-04385	742-04058
LpA/LwA/LwAg	86,6/98,8/100 dB (A)	85,9/98,6/100 dB (A)
Vibration value body / K-factor	1,6 / 0,6 m/s²	1,2 / 0,6 m/s²
Vibration value hand/arm / K-factor	2,6 / 1,3 m/s²	2,4 / 1,2 m/s²
Dimensions (L/W/H)	157 / 85 / 112 cm	192 / 86 / 112 cm
Net weight	126 kg	144 kg
Model number	13A726JD609	13A726SD609
EAN	4 008423 925135	4 008423 925142

You have the choice: side discharge ...

Do you have a large yard to mow and want the job done as quickly as possible? Then our Troy-Bilt® lawn tractors are your perfect choice. They are available with side or rear discharge technology, cutting widths from 92 to 107 cm and different transmission types and engines – including our top V-Twin with 679 cm³ displacement. Troy-Bilt® riders are practical, robust and reliable.



	PONY 92T-S	BRONCO 107T-S	HORSE 107T-S
Engine type	TROY-BILT	TROY-BILT	TROY-BILT V-TWIN
Engine displacement	439 cm³	547 cm³	679 cm³
Rated power	7,5 kW / 2450 min ⁻¹	9,0 kW / 2300 min ⁻¹	11,4 kW / 2400 min ⁻¹
Transmission / Speeds	Transmatic / 7 (f/b)	Automatic / variable (f/b)	Automatic / variable (f/b)
Tank volume (capacity)	3,8 l	3,8 l	3,8 l
Recommended lawn area* (up to)	4000 m²/h	5500 m²/h	5500 m²/h
Cutting width / height (min.-max.)	92 cm / 30–95 mm	107 cm / 30–95 mm	107 cm / 30–95 mm
Deck height adjustment	5 positions	5 positions	5 positions
Deck engagement	mechanical, by lever	mechanical, by lever	mechanical, by lever
Wash nozzle/Mulch Kit	–/Standard	Standard/Standard	Standard/Standard
Bag (capacity)	optional (19A300450EM)	optional (19A300310EM)	optional (19A300310EM)
Grass deflector	Standard	Standard	Standard
Turning radius	46 cm	46 cm	46 cm
Mow in reverse	–	Standard	Standard
Wheel size (f/r in inch)	15 x 6 / 20 x 8	15 x 6 / 20 x 8	15 x 6 / 20 x 8
Front Bumper	optional (OEM-190-679)	Standard	Standard
Headlights	Standard	Standard	Standard
Rear Hitch	Standard	Standard	Standard
Replacement blades	742-05629 (2x)	742-05177-L (2x)	742-05177-L (2x)
LpA/LwA/LwAg	85,6/98,8/100 dB (A)	85,4/98,7/100 dB (A)	85,3/98,7/100 dB (A)
Vibration value body / K-factor	0,4 / 0,2 m/s²	0,5 / 0,3 m/s²	0,4 / 0,2 m/s²
Vibration value hand/arm / K-factor	4,3 / 2,2 m/s²	4,4 / 2,2 m/s²	2,9 / 1,5 m/s²
Dimensions (L/W/H)	170 / 107 / 100 cm	170 / 115 / 100 cm	170 / 115 / 100 cm
Net weight	151 kg	175 kg	175 kg
Model number	13AB77B609	13A878BS609	13AJ78BS609
EAN	4 008423 924367	4 008423 924312	4 008423 924268

... or rear discharge mowing technology

Be flexible: our rear discharge models already come with a 240 l grass catcher included and a mulching kit is sold separately as an accessory. Cutting height can be adjusted in 5 positions between 30 and 95 mm and headlights help to get the job done even in low lighting conditions. All models have a small turning radius of only 46 cm to cope with even challenging terrain.



	PONY 92T-R	BRONCO 92T-R	HORSE 105T-R
Engine type	TROY-BILT	TROY-BILT	TROY-BILT V-TWIN
Engine displacement	439 cm³	547 cm³	679 cm³
Rated power	8,1 kW / 2700 min ⁻¹	10,1 kW / 2600 min ⁻¹	12,7 kW / 2700 min ⁻¹
Transmission / Speeds	Transmatic / 7 (f/b)	Hydrostatic / 1 (f/b)	Hydrostatic / 1 (f/b)
Tank volume (capacity)	3,8 l	3,8 l	3,8 l
Recommended lawn area* (up to)	3500 m²/h	3500 m²/h	4500 m²/h
Cutting width / height (min.-max.)	92 cm / 30–95 mm	92 cm / 30–95 mm	105 cm / 30–95 mm
Deck height adjustment	5 positions	5 positions	5 positions
Deck engagement	mechanical, by lever	mechanical, by lever	mechanical, by lever
Wash nozzle/Mulch Kit	–/optional (196-749A678, without blade)	Standard/optional (196-749A678, without blade)	Standard/optional (196-749A678, without blade)
Bag (capacity)	240 l	240 l	240 l
Grass deflector	optional (196-750A678)	optional (196-750A678)	optional (196-750A678)
Turning radius	46 cm	46 cm	46 cm
Mow in reverse	–	Standard	Standard
Wheel size (f/r in inch)	15 x 6 / 18 x 9,5	15 x 6 / 18 x 9,5	15 x 6 / 18 x 9,5
Front Bumper	optional (OEM-190-679)	Standard	Standard
Headlights	Standard	Standard	Standard
Rear Hitch	Optional	Optional	Optional
Replacement blades	742-04021A/742-04020A	742-04021A/742-04020A	742-04081/742-04080
LpA/LwA/LwAg	85,2/99,2/100 dB (A)	85,4/98,9/100 dB (A)	84,6/99/100 dB (A)
Vibration value body / K-factor	0,5 / 0,3 m/s²	0,5 / 0,3 m/s²	0,4 / 0,2 m/s²
Vibration value hand/arm / K-factor	3,6 / 1,8 m/s²	3,6 / 1,8 m/s²	1,7 / 0,85 m/s²
Dimensions (L/W/H)	225 / 99 / 103 cm	225 / 99 / 103 cm	225 / 110 / 103 cm
Net weight	196 kg	195 kg	198 kg
Model number	13AB77BE609	13A871BE609	13AJ71BN609
EAN	4 008423 924237	4 008423 924305	4 008423 924244

*Mowing performance depending on different conditions, e.g. terrain shape and slope, number of obstacles (trees, bushes), type of dischargement, length and humidity of the grasses etc.