

# DAFA ExFoil

Declaration of Performance acc. to EU 305/2011

Declaration of Performance no. 44 – 2018 R1	
1. Product type:	DAFA ExFoil
2. Identification of the product	Lot no. – see packaging
3. Intended use or uses of the product	Flexible sheets for waterproofing – Plastic and rubber vapor control layers, Type A
4. Name and contact address of the manufacturer	<b>DAFA A/S</b> Holmstrupgårdvej 12, DK-8220 Brabrand
5. Authorized representative	n/a
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 3
7. Notified body (hEN)	1939 and 0338
8. Notified body (ETA)	n/a

## 9. Declared performance Harmonized technical specification EN 13984

ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE
Length	EN 1848-2	m	50 (+1/-0)
Width	EN 1848-2	mm	2150 (+23/-7)
Mass per unit area (weight)	EN 1849-2	g/m <sup>2</sup>	140 (+14/-4)
Water tightness at 2kPa	EN 1928		Passed
Tensile strength (MD)	EN 12311-2	N/50mm	≥325
Tensile strength (CD)	EN 12311-2	N/50mm	≥250
Max. elongation (MD)	EN 12311-2	%	≥10
Max. elongation (CD)	EN 12311-2	%	≥10
Resistance to tearing by nail shank (MD)	EN 12310-1	N	≥200
Resistance to tearing by nail shank (CD)	EN 12310-1	N	≥200
Water vapor transmission Sd	EN 1931	m	20 (-4;+6)
Water vapor transmission after aging	EN 1931	m	Pass
Flame resistance	EN 13501-1		E



# DAFA ExFoil

Declaration of Performance acc. to EU 305/2011


The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4

Signed for and on behalf of the manufacturer by:

Brabrand, 09-10-2019

Jan Thuesen, Supplier Quality Engineer



A handwritten signature in blue ink, consisting of stylized, overlapping loops and lines, positioned above a horizontal dashed line.

