Product Information Sheet

commission i sources	DELEGATED REGU	LATION (EU) 2019/2	015 with regard to ener	gy labelling of light		
Supplier's name or trade mark: FESH						
Supplier's add	ress: Foss Europe	A/S, Åløkke Alle 7, 5	5000 Odense, DK			
Model identifier: Art.no.207001						
Type of light so	ource:					
Lighting techno	ology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		E27				
(or other electric interface)						
Mains or non-n		MLS	Connected light source (CLS):	Ja		
Colour-tuneabl		Nej	Envelope:	-		
High luminance light source:		Nej				
Anti-glare shield:		Nej	Dimmable:	Yes		
Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	F		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		806 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	30006500		
On-mode power (P _{on}), expressed in W		9,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,30		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,30	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80		
Outer	Height	60	Spectral power	See image		
dimensions without	Width	60	distribution in the	in last page		
Without	Depth	118		Sido 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Ja	If yes, equivalent power (W)	60			
		Chromaticity coordinates (x and y)	0,313 0,337			
Parameters for LED and OLED	light sources:		-,,,,,			
R9 colour rendering index valu	e 2	Survival factor	0,90			
the lumen maintenance factor	0,95					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,72	Colour consistency in McAdam ellipses	5			
Claims that an LED ligh source replaces a fluorescen light source without integrated ballast of a particular wattage.	t	If yes then replacement claim (W)	60			
Flicker metric (Pst LM)	0,4	Stroboscopic effect metric (SVM)	0,1			

(a)راً: not applicable;

(b)_{'-'}: not applicable;

