Rubiera, 01.11.2018



DECLARATION OF PERFORMANCE No. 0001RUBGRES

Unique identification code of the product type
Type, batch or serial number or any other element allowing identification of the product

Dry-pressed ceramic tiles, with water absorption Eb<=0,5%

2) Intended use(s)

For internal and external walls and flooring

- 3) Name or registered trade mark, and contact address of the manufacturer
 - Antica Ceramica Rubiera Via Salvaterra 18/A 42028 Rubiera (RE) Italy
- 4) System(s) of assessment and verification of constancy of performance (AVCP)

Systems 4

- Name and identification number of notified laboratory, if relevant –Not applicable Task(s) carried out AVCP system Document issued ad date of issue
- 6) Declared performance

Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	A1 FL/A1	
Release of dangerous substance, for:		
-Cadmium	NPD	
-Lead	NPD	
Breaking strength	>1 300 N	
Slipperiness:		
PTV Slider57,CENT/TS 16165:2011 Annex C	NPD	EN 14411:2016
Tactility	NPD	
Bond strength/adhesion, for:		
Cementitions adhesive type C2	1 N/mm²	
Thermal shock resistance	Pass	
Durability for:		
- Internal use	Pass	
- External use: freeze-thaw resistance	Pass	

The performance of the product identified is point 1 is in conformity with the declared performances is point 6. This declaration of performance is issued under the responsibility of the manufacturer identified in point 3. Signed for and on behalf of the manufacturer by Emanuele Frascari Amministratore Delegato

> (Stamp and Signature) Antica Ceramica Rubiera s.r.l. Vicalvatera 8/A - 42048 Burera (RE) Teo 0522.628841 - Fax 0522.628976 P.1. 01415260353 - C.F. 03793700372

Antica Ceramica Rubiera Srl Via Salvaterra, 18/a 42048 RUBIERA (RE) ITALY Codice fiscale 03793700372 Partita I.V.A. 01415260353 Internet: www.anticaceramica.it Tel. 0522-628841 - Fax 0522-628976

CE

Antica Ceramica Rubiera S.r.I. Via Salvaterra 18/A 42048 - Rubiera (RE) - Italy

05

0001 RUBGRES

EN 14411: 2012

Piastrelle di ceramica pressate a secco, con assorbimento di acqua E_b ≤ 0,5%, per pavimentazioni interne ed esterne