

NORDIC TECHNICAL DATASHEET

MADE IN BELGIUM

Nordic XL



20 years guarantee on residential use



Loc Life Time Guarantee



Matlook



4 bevels



Class 23
Class 32



Extra long boards



Extra large boards

PRODUCT DESCRIPTION

Dimensions

2033 L x 240 W x 8 TH mm

Packaging

Box: 5 boards - 2,44 m² (17,80 kg)

Pallet: 54 boxes - 131,74 m² (972,94 kg)

Composition

> surface layer

Paper impregnated with melamine resin

> Substrate

Moisture-resistant High Density Fibreboard, HDF

> Backing

Paper impregnated with melamine resin

Features

Matlook, MicroWoodview4, X-Long, X-Large

Installation

Best Loc X-treme: glue-free mechanical locking system with a short side droploc produced under license of Välinge Innovation AB, Flooring Industries Ltd and Faus Group Inc

Installation instructions

See box inlay or www.berryalloc.com

REQUIREMENTS

General requirements

According EN13329

Classification requirements

Class 23/32

CHARACTERISTICS

METHOD

TYPICAL VALUE

Abrasion resistance

EN 13329

IP₁ ≥ 4.000

Impact resistance

EN 13329

IC 2

Resistance to staining

EN 438

5 (groups 1 + 2);
4 (group 3)

Resistance to cigarette burns

EN 438

4

Effect of a furniture leg

EN 424

No damage
(foot type 0)

Effect of a castor chair

EN 425

No change in
appearance or damage

Thickness swelling

EN 13329

≤ 18%

CE - CLASSIFICATION ACCORDING EN14041

Fire resistance

C_{fl}-S1

Formaldehyde

E1

Slipperiness

DS

OTHER TECHNICAL DATA

Sustainability of forests

PEFC certified (07-31-229)

Labelling according to French VOC emission regulation

A+

Floor heating

See specific instructions at www.berryalloc.com

Thermal resistance in combination with underlay Excellence Endurance

0,10 m² K/W

WARRANTY AND MAINTENANCE

Residential warranty

20 years

Warranty conditions

See www.berryalloc.com

Care and maintenance

See www.berryalloc.com