

CERTIFIKAT

CERTIFICATE



**GODKENDT
TIL DRIKKEVAND**

Dette certifikat er udstedt i henhold til bekendtgørelse nr. 1007 af 29. juni 2016 om markedsføring og salg af byggevarer i kontakt med drikkevand. Certifikatet giver godkendelsesindehaveren rettighed til at markedsføre og sælge nedenstående byggevarer i Danmark og til at mærke byggevarerne med "Godkendt til drikkevand"-mærkningen.

This certificate is issued according to Executive Order no. 1007 of 29 June 2016 on the placement on the market and sale of building components that come into contact with drinking water. The certificate gives the approval holder the rights to market and sell the following building component in Denmark and to mark the building component with the "Godkendt til drikkevand" marking.

GODKENDELSE NR. / APPROVAL NO.:

01/00021

UDSTEDT / DATE OF ISSUE:

29-05-2018

UDLØBER / EXPIRY DATE:

28-05-2023

GODKENDELSESINDEHAVER / APPROVAL HOLDER:

**Yuhuan Jianglin Plumbing Hose & Parts Co., Ltd
Packaging Industrial Zone, Yuhuan
317608 Taizhou, Zhejiang Province
CN, China**

BYGGEVARE / BUILDING COMPONENT:

KOMBI FLEX / JL KOMBI FLEX



BETINGELSER FOR GODKENDELSE:

De nærmere betingelser og vilkår for godkendelsen er fastsat i bekendtgørelse nr. 1007 af 29. juni 2016 om markedsføring og salg af byggevarer i kontakt med drikkevand. Endvidere henvises til godkendelsesbrev af 29-05-2018 om godkendelse af ovennævnte byggevarer i kontakt med drikkevand og eventuelle senere ændringer til godkendelsesbrevet fremsendt til godkendelsesindehaver. Markedsføring og salg af byggevarerne efter nærværende godkendelse omfatter de versioner af byggevarerne, der er opført i bilaget, og den variantproduktion, der er angivet i bilaget.

CONDITIONS OF APPROVAL:

The detailed terms and conditions of approval are laid down in Executive Order no. 1007 of 29 June 2016 on the placement on the market and sale of building components in contact with drinking water. See also the approval letter of 29-05-2018 on the approval of the above-mentioned building component in contact with drinking water, and any subsequent amendments to the approval letter submitted to the approval holder. Marketing and sale of the building component under this approval include the versions of the building component listed in the Annex and the "on-demand" production specified in the Annex.

CERTIFIKATET ER UDSTEDT AF:

THE CERTIFICATE IS ISSUED BY:

Trafik-, Bygge- og Boligstyrelsen

Danish Transport, Construction
and Housing Authority

Edvard Thomsens Vej 14

2300 København S

Mail: GDV@tbst.dk

Web: www.tbst.dk

København, den 29-05-2018

Birgitte Lundblad

Kontorchef / Head of division

BILAG / ANNEX

GODKENDELSE NR. / APPROVAL NO.:

01/00021

VERSIONER AF BYGGEVAREN OMFATTET AF GODKENDELSEN: VERSIONS OF THE BUILDING COMPONENT COVERED BY THE APPROVAL:

OVERORDNEDE INFORMATIONER OM BYGGEVAREN GENERAL INFORMATION ABOUT THE BUILDING COMPONENT

BYGGEVAREN:
BUILDING COMPONENT:

KOMBI FLEX / JL KOMBI FLEX

VERSIONER VERSIONS

VARETEKST:
ITEM TEXT:

DIMENSION:
DIMENSION:

SLANGER:
HOSE:

PEX Hose

DN6 min. 100mm - max 2000mm

PEX Hose

DN8 min. 100mm - max 2000mm

FITTINGS:
FITTINGS:

Straight inserter DN6, DN8.

12-65mm

3/8" 12-65mm

Straight inserter DN6, DN8. Female nut

1/2" 12-65mm

3/4" 12-65mm

Straight inserter DN6, DN8. Male thread

3/8" 12-65mm

1/2" 12-65mm

3/4" 12-65mm

M8 12-110mm

| | | |
|---|---------------|--------------------------------|
| | M10 12-110mm | |
| | M12 12-110mm | |
| Straight inserter DN6, DN8. Tube | Ø8 12-65mm | |
| | Ø10 12-65mm | |
| | Ø12 12-65mm | |
| Straight inserter DN6, DN8. Compression fitting | Ø8 12-65mm | |
| | Ø10 12-65mm | |
| | Ø12 12-65mm | |
| | Ø15 12-65mm | |
| Elbow inserter DN6, DN8. Female nut | 3/8" 12-110mm | |
| | 1/2" 12-110mm | |
| | 3/4" 12-110mm | No. FL3040034021 (testversion) |

PRODUKTSPEKTER FOR OMFATTEDE VARIANTPRODUKTER - SLANGER

PRODUCT RANGE FOR "ON-DEMAND" VARIANTS INCLUDED - HOSE

| | | |
|-------------------------|------------------------------|---------|
| DN DN | MINDSTE: SMALLEST: | DN6 |
| | STØRSTE: LARGEST: | DN8 |
| LÆNGDE LENGTH | MINDSTE: SMALLEST: | 100 mm |
| | STØRSTE: LARGEST: | 2000 mm |

PRODUKTSPEKTER FOR OMFATTEDE VARIANTPRODUKTER - FITTINGS

PRODUCT RANGE FOR "ON-DEMAND" VARIANTS INCLUDED - FITTINGS

| | | |
|-------------------------|------------------------------|--------|
| DN DN | MINDSTE: SMALLEST: | DN6 |
| | STØRSTE: LARGEST: | DN8 |
| LÆNGDE LENGTH | MINDSTE: SMALLEST: | 12 mm |
| | STØRSTE: LARGEST: | 110 mm |